

General Relay

Main technical parameter

Model		60.12	60.13	60.12- I
Specifications				
Terminal layout		2Z	3Z	2Z
Contact capacity	AC	10A 220V	10A 220V	10A 250V
	DC	10A 28V	10A 28V	10A 30V
Contact resistance(mΩ)		≤50mΩ	≤50mΩ	≤50mΩ
Insulation resistance(MΩ)		≥500MΩ	≥500MΩ	≥500MΩ
Dielectric strength	BOC	2000VAC	2000VAC	1500VAC
	BCC	2000VAC	2000VAC	1500VAC
Coil nominal voltage	AC	6 to 240V	6 to 240V	6 to 380V
	DC	6 to 125V	6 to 125V	6 to 220V
Coil nominal power	AC	≤3.5VA	≤3.5VA	2.0VA to 2.8VA
	DC	≤2W	≤2W	≤1.5W
Electrical life(OPS)		20 ⁵	20 ⁵	10 ⁵
Mechanical life(OPS)		20 ⁷ /50 ⁷	20 ⁷ /50 ⁷	10 ⁷
Operating temperature(°C)		-40~+70	-40~+70	-40~+60
Weight(g)		≤125	≤125	≤80
Mounting methods		Outlet	Outlet	Outlet



Dimension

