

Combination Switched Sockets

500V combination switched sockets

All 500V Switched Sockets rated 32A and above have an internal interlocking feature (plugs cannot be withdrawn or inserted when the switch is in the ON position. This feature is also available for 16A and 20A upon request.

Optional keylocking OFF facility(quote"cvk"when ordering keylock type, e.g.cat no.56CVK432).

For NEON indicator option add "N" after catalogue number.



Catalogue Number	56CV 416	56CV 416K	56CV 420	56CV 432	56CV 435	56CV 440	56CV 450	56CV 516	56CV 520	56CV 532	56CV 535	56CV 540	56CV 550	56CV 616	56CV 716	56CV 720
Rated Operational Voltage Ue(-50Hz) Volts	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500
Rated Thermal Current Enclosed Amps	16	20	32	35	35	40	50	16	20	32	35	40	50	16	16	20
SWITCH Description	3Pole	3Pole	3Pole	3Pole	3Pole	3Pole	3Pole	3Pole	3Pole	3Pole	3Pole	3Pole	3Pole	3Pole	3Pole	3Pole
Utilisation Category Amps	16AX M120	20AX M180	32AX M180	32AX M250	32AX M250	50AX M250	50AX M120	16AX M150	20AX M160	32AX M180	32AX M250	50AX M250	50AX M120	16AX M120	16AX M120	20AX M150
AS3133 250V kW	7.5	11.0	15.0	15.0	15.0	18.5	18.5	7.5	11.0	15.0	15.0	18.5	18.5	7.5	7.5	11.0
AC23A 240V Amps	15	21	28	28	28	35	35	15	21	28	28	35	35	15	15	21
Cable Cross Section Min	1	1	1	1	1	1	6	6	1	1	1	6	6	1	1	1
Solid or Stranded mm2 Max	16	16	16	16	16	16	35	35	16	16	16	35	35	16	16	16
SOCKET																
Number of socket Pins Including (Earth)	4	4	4	4	4	4	4	5	5	5	5	5	5	6	7	7
Socket Configuration																
IP Rating	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66