

LLJSX Double-Side Travel Limit Appliance 系列双向(单向)行程限位器行程开关

适用范围Application

LLJSX系列双向行程限位器应用于建筑、港口、矿山等行业的起重，传输机械的空间三座标的控制和限位。具有体积小、功能多、精度高、限位可调、通用性强及维护安装和使用调正方便等优点。限位器采用可调试机械记忆结构，具有性能可靠、灵敏度高等特点。

LLJSX series Double-side Travel Limit Appliance is widely used in Architecture, Shipping Port, Mine fields. It is used to control and limit the chain block and transmission machine's room tri-coordinates. It has some characters as sensitive structure, small volume, multi-function, high accuracy, moveable, strong communicate and installation convenience.

The Limit Appliance adopt moveable mechanical form, has performance credibility and high acuity characters.

主要技术参数

工作环境: -40~+50℃
 相对温度: 不大于90%
 海拔高度: 不大于2500M
 电压: AC380V
 额定电流: 6A
 控制回路: 2回路
 标准传动比:
 传动比: 1:270 1:126 1:65 1:60 1:22
 1:92 1:46 1:176 1:40 1:21 1:16 1:30

Main Technology Data

Working condition: -40~+50℃
 Relative Temperature: 90% or less
 Elevation: below 2500M
 Voltage: 380V
 Rating Current: 6A
 Circuit Controlling: 2 Circuit
 Standard Drive Rate:
 Drive Rate: 1:270 1:126 1:65 1:60
 1:92 1:46 1:176 1:40 1:21 1:16 1:30

LLJSX

