

## Tools Series

### HS-30J

For suage connectors  
Capacity mm<sup>2</sup>:0.5-6.0  
Length mm:230  
Weight kg:0.6



### HS-10

For non-insulated cable links  
Capacity mm<sup>2</sup>:1.5-6.0  
Length mm:230  
Weight kg:0.6



### HS-04WF

For wire-end ferrules  
Capacity mm<sup>2</sup>:1.0-6  
Length mm:230  
Weight kg:0.6



### HS-101

For non-insulated cable links  
Capacity mm<sup>2</sup>:1.0-10  
Length mm:230  
Weight kg:0.6



### HS-03B

For non-insulated plug connectors 4.8+6.3mm  
Capacity mm<sup>2</sup>:1.0-4.0  
Length mm:230  
Weight kg:0.6



### HS-04WFL

For wire-end ferrules  
Capacity mm<sup>2</sup>:0.5-4  
Length mm:230  
Weight kg:0.6



### HS-26TW

For wire-end ferrules  
Capacity mm<sup>2</sup>:0.5-6  
Length mm:230  
Weight kg:0.6



### HS-35WF

For wire-end ferrules  
Capacity mm<sup>2</sup>:10.0-35.0  
Length mm:230  
Weight kg:0.6



### HS-06WF2C

For wire-end ferrules+insulated cable links  
Capacity mm<sup>2</sup>:0.5-2.5  
Length mm:230  
Weight kg:0.6



### LY-03C

For insulated cable links+butt connectors  
Capacity mm<sup>2</sup>:0.5-6  
Length mm:230  
Weight kg:0.6



### HS-103/LY-13C

Capacity mm<sup>2</sup>:0.5-6 for insulated closed terminals  
Length mm:230  
Weight kg:0.6



### HS-05FL HS-06FL

For tab 90° Flag Terminals  
Capacity mm<sup>2</sup>:4.8mm  
Length mm:250  
Weight kg:0.55



### HS-07FL

For Tab 90° Flag Terminals  
Capacity mm<sup>2</sup>:1.25-2.5  
Length mm:230  
Weight kg:0.55



### HS-02H

For Crimpingrg Type Cable  
Length mm:230mm  
Weight kg:0.6kg



### HS-05H

For Crimpingrg Type Cable  
Length mm:230mm  
Weight kg:0.6kg



### AP-03C

For insulated cable links+butt connectors  
Capacity mm<sup>2</sup>:0.5-6.0  
Length mm:250  
Weight kg:0.55



### AP-03B

For non-insulated plug connectors  
Capacity mm<sup>2</sup>:1.0-4.0  
Length mm:250  
Weight kg:0.55



### AP-04WFL

For wire-end ferrules  
Capacity mm<sup>2</sup>:0.5-4.0  
Length mm:250  
Weight kg:0.55



### AP-26TW

For wire-end ferrules  
Capacity mm<sup>2</sup>:2×0.5-6  
Length mm:250  
Weight kg:0.55



### AP-30J

For insulated cable links+butt connectors  
Capacity mm<sup>2</sup>:0.5-6.0  
Length mm:250  
Weight kg:0.55

