

Tools Series

AP-02H

For conductor SW 5.4+SW 6.48 for screen COAX connectors



AP-457

For conductor SW 5.4+SW 6.48 for screen COAX connectors



AP-10

For non-insulated cable links
Capacity mm²: 1.5-6.0
Length mm:250
Weight kg:0.55



AP-101

For non-insulated cable links
Capacity mm²:1.0-10.0
Length mm:250
Weight kg:0.55



AP-05FL AP-06FL

For Tab 90° Flag Terminals
Capacity mm²: 6.3mm
Length mm:250
Weight kg:0.55



AP-07FL

For Tab 90° Flag Terminals
Capacity mm²: 1.5-2.5
Length mm:250
Weight kg:0.55



HSC8 6-4

Capacity mm²:0.25-6.0
Length mm:175
Weight kg:0.36



HSC8 6-6

Capacity mm²:0.25-6.0
Length mm:175
Weight kg:0.36



HSC8 1-4

Capacity mm²:0.08-2.5
Length mm:175
Weight kg:0.36



HSC8 2-4

Capacity mm²:0.14-6.0
Length mm:175
Weight kg:0.36



HS-1MA

For Non-insulated cable links
Capacity mm²:1.25-2.5
Length mm:170
Weight kg:0.25



HSC8 16-4

Capacity mm²:6.0-16.0
Length mm:210
Weight kg:0.52



HS-0725

FOR INSULATED TERMINALS AND CONNECTS
Capacity mm²:1.0-2.5
Length mm:203
Weight kg:0.4



HS-11011

For Non-insulated plugs connectors
Capacity mm²:0.1-2.5
Length mm:203
Weight kg:0.4



HS-0325

For non-insulated cable links
Capacity mm²:0.5-2.5
Length mm:203
Weight kg:0.4



HS-05WF

For wire-end freeules
Capacity mm²:0.5-6
Length mm:203
Weight kg:0.4



HS-06WF

For wire-end freeules
Capacity mm²:0.25-6
Length mm:203
Weight kg:0.4



HS-16WF

For wire-end freeules
Capacity mm²:6-16
Length mm:203
Weight kg:0.4



HS-02WF2C

Capacity mm²:0.5-2.5
For wire-end freeules+insulated cable link
Length mm:203
Weight kg:0.4

