

SC AC Contactor



SC-0



SC-05



SC-4-0



SC-5-1




SC-1N



SC-3N



SC-4N



SC-5N

Specification

Type		SC-03	SC-0	SC-05	SC-4-0	SC-4-1	SC-5-1
Max.vole of motor	200-240V	2.5	3.5	3.5	4.5	5.5	5.5
	380-440V	4	5.5	5.5	7.5	11	11
	500-550V	4	5.5	5.5	7.5	11	11
	600-660V	4	5.5	5.5	5.5	7.5	7.5
Operating current AC3(A)	200-240V	11	13	13	18	22	22
	380-440V	9	12	12	16	22	22
	500-550V	7	9	9	13	17	17
	600-660V	5	7	7	9	9	9
Rated heating current (A)		20	20	20	25	32	32
Aux-contact layout	Standand	1NO	1NO	1NO 1NC	1NO	1NO 1NC	2NO 2NC
	Other	1NC	1NC	2NC 2NC	1NC	2NC	2NO 2NC
Life of probability (x10 ⁴)	Electrical	200	200	200	150	200	200
	Machanical	1000	1000	1000	1000	1000	1000

Type		SC-1N	SC-2N	SC-2SN	SC-3N	SC-4N	SC-5N	SC-6N
Max.vole of motor	200-240V	7.5	11	15	18.5	22	30	37
	380-440V	15	18	22	30	40	55	60
	500-550V	15	18	25	37	37	55	60
	600-660V	11	15	22	30	37	55	60
Operating current AC (A)	200-240V	27	39	52	65	80	105	126
	380-440V	30	37	48	65	80	105	120
	500-550V	24	29	38	60	60	85	90
	600-660V	15	19	26	38	44	64	72
Rated heating current (A)		50	60	80	100	135	150	150
Aux-contact layout	Standand	2NO 2NC	2NO 2NC	2NO 2NC	2NO 2NC	2NO 2NC	2NO 2NC	2NO 2NC
	Other	4NO 4NC	4NO 4NC	4NO 4NC	4NO 4NC	4NO 4NC	4NO 4NC	4NC 4NC
Life of probability (x10 ⁴)	Electrical	200	200	200	200	100	100	100
	Machanical	1000	1000	500	500	500	500	500