

Insulation Piercing Connectors

Four-core collecting stran clamp(0.6/1kV)



GB1 16-50mm²

GB2 70-120mm²

Clamp CT3

Clamp CT1

CT2

CT4



TE1 Single screw

TE2 Double screw

Product type and application scope 1kV Series products

the section plane of main wire	the section plane of branch	Max.load current	Exterior dimension
16~95	1.5~10	63	27x41x62
16~95	4~35(50)	138	46x52x87

Industrial Plugs

INSULATED CLAMP



2.1

2.2

1.1A

1.1B

Code	Conductor range
2.1	25-70mm ²
2.2	70-120mm ²
1.1A	25-120mm ²
1.1B	25-120mm ²

Piercing Connector



IPC 3.1

IPC 3.2

IPC 3.3

IPC 3.4

TTD 121F

TTD 201F

TTD 281F

TTD 451F

Code	Conductor Range(mm ²)		No.Bolt
	Main	Tap	
IPC3.1	95-16	25-10	1
IPC3.2	95-70	95-70	1
IPC3.3	185-120	25-16	1
IPC3.4	185-70	185-70	2
TTD121F	AL-CU	16-50	1
TTD201F	95-70	95-70	1
TTD281F	185-120	25-10	1
TTD451F	185-120	185-70	2