

NF-SW, CW Moulded Case Circuit Breaker



Main technical specifications					
Frame rated current $I_{nm}(A)$		32	63	125	
Type		NF30-SW,CW	NF63-SW,CW	NF125-SW,CW	
Rated current $I_n (A)$ 40°C reference ambient temperature		6, 10, 16, 20, 25, 32	6, 10, 16, 20, 25, 32, 40, 50, 63	60, 75, 100, 125	
Number of poles		2, 3	2, 3	2, 3	
Max rated service voltage $U_i(V)$		AC	690	690	
		DC	250	250	
Dimensions and mounting details		a	67.5	75	90
		b	96	130	130
		c	49	68	61
		ca	67	88	88
		bb	84	110	110
		aa	23.5	25	30
		Frame rated current $I_{nm}(A)$		250	400
Type		NF250-SW	NF400-SW	NF630-SW	
Rated current $I_n (A)$ 40°C reference ambient temperature		125, 150, 175, 200, 225, 250	250, 300, 350, 400	500, 600, 630	
Number of poles		2, 3	3	3	
Max rated service voltage $U_i(V)$		AC	690	690	
		DC	250	250	
Dimensions and mounting details		a	105	140	210
		b	140	257	275
		c	61	97	97
		ca	92	135	155
		bb	126	194	243
		aa	35	44	70
		NF800-SW,CW 3P	NF1000-SW,CW 3P	NF1250-SW,CW 3P	