

## KD-L Earth Leakage Circuit Breaker

### Application

KD-L server earth leakage circuit breaker is used to AC 230V,50Hz rarent to 30A, it used to boby electricity and overload protection it used to prevent from fire risk dllo to device destory .

It also used to protect wire overwad ctype 1and type3 must use with fuse cut-out.

This earth leakage ciecuit breaker is AC electroinc snap-action type.The product is complied with IE(755-1922 and GB6829-1955,GB16916,1-1997 standard).The production win “CCC” CQC certificate.



KD-L2123J (NEW)



KD-L2123J COVER



KD-LS2123

### Specification and technical data

ELCB basic parameter

Rated Voltage (V)	Frequency (Hz)	pole	Rated Current(A)		Rated Sensitivity Current (mA)	Rated Non-Sensitivity Current (mA)	Operating Time(s)	
			with load trip (A)	without load trip(A)			I Δ n	0.25A
220-240	50-60Hz	2	10,16,20,30	20,30	30,15,10	15,7,5,6	0.1	0.04

Serial No.	Examination Current	Incept State	Examination Current
1	1.13In	cold	t ≥ 1h non Actuation
2	1.45In	hot	t < 1h Actuation
3	2.55In	cold	1 < t < 60s Actuation

### Dimensions(mm)

