

ID Earth Leakage Circuit Breaker



ID-2P

ID-4P



IDN-2P

IDN-4P

Type	Width in mold of 9mm	Rat (A)	Sens(mA) 50Hz	Cat.NO CEE27 ID 240V	BS4293 RCCB 240V		
2P	4	16	10	23008	23081		
			25		23009	23082	
		40	30	23011	23083		
			300	23014	23086		
			30	23015	23088		
			100	23016			
		63	300	23017	23090		
			500	23018			
			30	23021	23093		
			100		23094		
		80	300	23022	23095		
			500				
			30	23030	23097		
			100		23098		
			300	23033	23099		
			500				
100	4	30	23034	23101			
				100	23102		
		300	23035	23103			
		500		23116			
		4P	8	25	30	23118	
					300	23121	
				40	30	23042	23123
					100	15176	
					300	23045	23125
					300	23062	
63	500			23046			
	500			23063			
	30			23047	23128		
	10			15177	23129		
80	300	23049	23120				
	300	23066	23146				
	500	23067					
	300	23054					
100	300	23069					
	300	23056					
	300	23059					
	300						

PG230/430 DBR230/430 DDC230 Earth Leakage Circuit Breaker



PG230



PG430



DBR230



DBR430



DDC230

Specification

Type	PG230	PG430	DBR230	DBR430	DDC230
Poles	2P	4P	2P	4P	2P
Rated voltage (V)	250V/440V		250V/440V		
Rated current (A)	10,15,20,25,30,45,50,60A Adjustable		5A-15A, 10-30A, 30-60A Adjustable		
Leakage motion current (mA)	300mA,500mA	300mA,500mA	300mA	500mA	1000mA
Leakage dead current (mA)	150mA,250mA	150mA,250mA	150mA	250mA	500mA
Accord with standard	NFC 61450		NFC 61450		